Portable Autoclave



ST-P18 ST-P24



ST-P18B ST-P24B

Advantage

- High-quality stainless steel body construction for durability and longevity.
- Self-inflating type seal for effective sealing during operation.
- Electric heating mode for efficient and controlled heating.(For model:ST-P18, ST-P24)
- Dual heating options: electric and gas.(For model:ST-P18B, ST-P24B)
- Automatic release when overpressure occurs, with low water level protection to prevent dry burning.
- Double scale indication pressure gauge for accurate monitoring and measurement.

Specification

Model	ST-P18	ST-P24	ST-P18B	ST-P24B
Capacity (L)	18	24	18	24
Rated Working Temperature	126°C			
Rated Working Pressure	0.142MPa			
Temp Accuracy	±1°C			
Consumption	2.0kW			
Power Supply	220V/110V, 50Hz/60Hz			
Chamber Size (Ø×H) (mm)	280×295	280×390	280×295	280×390
Shipping Size (W×D×H) (mm)	410×440×560	410×410×680	420×420×430	420×420×540
N.W./G.W. (kg)	16/17	17.5/19	15/16	16/18

Portable Autoclave



Advantage

- Microcomputer control with digital display, adjustable sterilization temperature and time.
- All Stainless Steel 304 body construction for durability and longevity.
- Overpressure auto-release for enhanced safety.
- Clear and easy to read double scale pressure gauge.
- Self-inflating seal for secure and reliable operation.
- Simple operation with a focus on safety and reliability.

Specification

Model	ST-P18E	ST-P24E
Capacity	18L	24L
Rated Working Temperature	126°C	
Rated Working Pressure	0.142MPa	
Temp Accuracy	±1°C	
Consumption	2.0kW	
Power Supply	220V, 50/60Hz	
Chamber Size (Ø×H)	280×295mm	280×390mm
Shipping Size (W×D×H)	420×420×560mm	420×420×680mm
N.W./G.W.	17/18kg	17.5/19kg